

LYNX 2100

La série des tours horizontaux compacts LYNX 2100 est idéale pour l'usinage de petites pièces. L : Banc long - M : Outils tournants

S : Broche de reprise

Machine	Ø Mandrin (mm)	Ø de tournage max. (mm)	Longueur Usinable Max. (mm)	Vitesse de broche (tr/min)	Moteur (Kw)
LYNX 210A / B	170 / 210 mm	280	280 / 300 mm	6000 / 5000	15 / 15 / 11
LYNX 2100A / LA	170 mm	350	330 / 550 mm	6000	15 / 15 / 11
LYNX 2100B / LB	210 mm	350	330 / 550 mm	4500	15 / 15 / 11
LYNX 2100LC	255 mm	350	537 mm	3500	18.5 / 18.5 / 15
LYNX 2100MA / LMA	170 mm	300	290 / 510 mm	6000	15 / 15 / 11
LYNX 2100LMC / LMSC	255 mm	300	497 mm	3500	18.5 / 18.5 / 15
LYNX 2100LMSA	170 mm	300	510 mm	6000	15 / 15 / 11
LYNX 2100LMSB	210 mm	300	510 mm	4500	15 / 15 / 11
LYNX 2100YA / YB	170 / 210 mm	300	300 mm	6000 / 4500	15 / 15 / 11
LYNX 2100LYA / LYB	170 / 210 mm	300	510 mm	6000 / 4500	15 / 15 / 11
LYNX 2100LSYA / LSYB	170 / 210 mm	300	510 mm	6000 / 4500	15 / 15 / 11
LYNX 2100G super	170 mm	-	330 mm	6000	15 / 15 / 11
LYNX 300	255 mm	450	765 mm	3500	15 / 15 / 11
LYNX 300M	255 mm	370	712 mm	3500	15 / 15 / 11

